## **AMENDMENTS TO THE CLAIMS**

Docket No.: HO-P03292US0

Claims 1-6 (Cancelled)

- 7. (Cancelled)
- 8. (Cancelled)
- 9. (Currently amended) The environmentally friendly package according to claim 714, wherein the package is a beverage making capsule that contains a beverage making ingredient.
- 10. (Previously presented) The environmentally friendly package according to claim 9, wherein the capsule further comprises a compostable filter sheet inside the capsule and bonded to an internal surface of the capsule.
- 11. (Cancelled)
- 12. (Cancelled)
- 13. (Cancelled)
- 14. (New) An environmentally friendly package comprising:

  two compostable sheets, each sheet comprising an outer substrate layer and an inner multilayer sealing film, the inner sealing film having a core of a high-melting-point and a surface layer of a lower melting point, the sheets each having a top and bottom seam and side edge seams, wherein the two sheets are bonded together in a face-to-face relationship in which the top and side edge seams are bonded together with a high sealing strength using temperatures higher than 160° C and the bottom seams are bonded with a low sealing strength using temperatures of about 100° C to 150° C.

2

65463108.1

Application No. 10/572,727 Amendment dated March 26, 2010

Response to Office Action of January 24, 2010

15. (New) The environmentally friendly package according to clam 14, wherein a nozzle is inserted into the top seam.

Docket No.: HO-P03292US0

- 16. (New) The environmentally friendly according to claim 14, wherein the peel strength of the region of sealing having the low heat sealing strength is in the range of 2N to 30N.
- 17. (New) The environmentally friendly according to claim 16, wherein the peel strength of the region of sealing having the low heat sealing strength is in the range of 5N to 20N.
- 18. (New) The environmentally friendly according to claim 14, wherein the peel strength of the region of sealing having the higher sealing strength is greater than 30N.
- 19. (New) The environmentally friendly according to claim 18, wherein the peel strength of the region of sealing having the higher sealing strength is greater than 50N.
- 20. (New) The environmentally friendly according to claim 14, wherein at least on of the compostable sheets is laminated.
- 21. (New) The environmentally friendly according to claim 14, wherein a flexible reinforcing strip is attached along the bottom seam to provide more controlled opening of the seam.
- 22. (New) A method of manufacture of an environmentally friendly package comprising the steps of:

providing a compostable sheet material comprising an outer compostable outer substrate layer and an inner multilayer sealing film, the sealing film having a core of a

65463108.1

high-melting-point and a surface layer of a lower melting point, the sheet material having a top, bottom and side edges;

Docket No.: HO-P03292US0

placing two webs of the compostable sheet material together with the inner films in a face-to-face relationship; and

sealing the in top, bottom and side edges together to form seams in which the top and side edges are bonded together with a high sealing strength using temperatures higher than 160° C and the bottom seams are bonded with a low sealing strength using temperatures of about 100° C to 150° C.

- 23. (New) The method of manufacture according to claim 22, wherein the peel strength of the region of sealing having the low heat sealing strength is in the range of 2N to 30N.
- 24. (New) The environmentally friendly according to claim 22, wherein the peel strength of the region of sealing having the higher sealing strength is greater than 30N.
- 25. (New) The method of manufacture according to claim 22, further including the step of inserting a nozzle into the top seam.
- 26. (New) The method of manufacture according to claim 22, further including the alternate step of folding over a single compostable sheet so that the inner film is in a face-to-face relationship prior to sealing the edges.

65463108.1 4